

## 2009 Reno Region Track Trials Safety Inspection Check

Driver/Entrant \_\_\_\_\_ Date \_\_\_\_\_ Annual \_\_\_\_\_

Car # \_\_\_\_\_ Class \_\_\_\_\_ Make \_\_\_\_\_ Model \_\_\_\_\_

Color \_\_\_\_\_ Scrutineer \_\_\_\_\_ Yes No

<b>A. Logbook complete and up to date. Car eligible for class.</b>		
<b>B. Appearance suitable for competition. Neat &amp; clean with no ex-</b>		
<b>C. Tires—120 mph rated or better not showing cord.</b>		
<b>D. Brakes-Pedal operated working directly on all four wheels-Good</b>		
<b>E. Body panels securely mounted, Trim rings &amp; hub caps removed.</b>		
<b>F. Exhaust System-directed away from body &amp; terminate behind a</b>		
<b>G. Hood &amp; Engine compartment-Securely fastened. Battery securely mounted with positive terminal covered. Throttle return consistent</b>		
<b>H. Suspension &amp; Steering-Suitable design and good working order</b>		
<b>I. Leakage &amp; Caps-No visible leaks. Monza (flip top) gas caps pro-</b>		
<b>J. Lights-Brake lights on cars so equipped and taillights on formula</b>		
<b>K. Seats-seat shall be securely mounted. If a folding seat the back shall be securely bolted or strapped in place. A one piece bucket type race seat is highly recommended including an upper brace if non-FIA homologated.</b>		
<b>L. Seat belts &amp; Shoulder Harness-Shall conform to TTR section 10.20.7 and Section 12.</b>		
<b>M. Tonneau covers and Boot covers shall be removed.</b>		
<b>N. Firewall and Floor-Shall comply with Section 10.18.</b>		
<b>O. Mirrors-Shall provide driver visibility to the rear on both sides of the car.</b>		
<b>P. Drivers Safety Equipment shall comply with Section 10.20. The scrutineer shall affix a dated non-removable decal to helmets which comply with Section 10.20.2.</b>		
<b>Q. Holding tanks and engine, transmission breathers shall comply with Section 10.23.</b>		
<b>R. Wood rim steering wheels prohibited.</b>		

## 2009 Reno Region Track Trials Safety Inspection Continued

	<u>Yes</u>	<u>No</u>
<b>S. The driver shall not be exposed to header tanks or unshielded fuel, oil or coolant lines. Braided steel lines are considered to be shielded.</b>		
<b>T. Windows shall be clear or uncolored. Officials may require replacement of windshields that are considered a safety hazard.</b>		
<b>U. Non-metallic wheel construction is prohibited. Non-metallic chassis construction is prohibited except in ASR, CSR, DSR, S2000, FA and Hill-climb Specials.</b>		
<b>V. The mounts for video/photographic cameras shall be of a safe and secure design and subject to the approval by the Chief Tech and Safety Steward. Helmet mounted cameras may be approved on an individual basis.</b>		
<b>W. Cool suits are allowed in all classes. Water tank mounts shall be of a safe and secure design.</b>		
<b>X. Data collection devices are considered to be instrumentation and are therefore allowed in all classes that permit the installation, replacement or addition of gauges, indicators or instruments.</b>		
<b>Y. On all carburetors, (except SU, C and D Sport Racers with motorcycle type carburetors and Formula 500 with Mikuni VM38) with a non threaded fitting shall be replaced by drilling and tapping the carburetor body for a threaded fitting.</b>		